



## IR 3.5MM KEYSTONE JACK

- Allows for IR Extension without Splicing
- Compatible with Leviton, ICC, Allen Tel and Many Others
- Tool-Less Design
- Spring Loaded Terminals (back side)
- Accepts up to 20 AWG Cable
- Note: This over-sized connector is compatible with Vanco's full size Datacom Wall Plates. Not Décor type



PART #	PKG.
280752	PKGD

## IR 3.5MM IN-LINE JACK

- Allows for IR Extension without Splicing
- In-line 3.5 mm (1/8") Stereo Cable Connector
- Designed for quick - easy 3.5mm Stereo Jack connector assembly
- Tool-Less Design
- Spring Loaded Terminals (one side)
- Accepts up to 20 AWG Cable



PART #	PKG.
280753	PKGD

## IR BRASS TUBE RECEIVER


- Ideal for installation in areas illuminated by compact fluorescent lighting (CFL)
- 10 ft pigtail with 3.5 mm plug
- IR Receive Frequency: 34 kHz to 60 kHz
- IR Transmit Frequencies: 38 kHz & 56 kHz
- Range: 40 ft at 38 kHz & 25 ft at 56 kHz
- Dimensions: 0.96" L x 0.65" OD
- Brass Finish



PART #	PKG.
280736	PKGD

## IR KEYSTONE RECEIVER

- Compatible with Keystone Face Plates
- Can be connected with the use of 18 AWG 2 or 4 Conductor Low Voltage Wire or Cat5e/Cat6 Cable
- IR Receive Frequency: 34 kHz to 60 kHz
- IR Transmit Frequencies: 38 kHz & 56 kHz
- Range: 40 ft at 38 kHz & 25 ft at 56 kHz
- Dimensions: 1.55" L x .75" W x 1" H



PART #	PKG.
280737	PKGD

## DUAL BAND IR RECEIVER

- IR Receive Frequency: 34 kHz to 60 kHz
- IR Transmit Frequencies: 38 kHz & 56 kHz
- Range: 40 ft at 38 kHz & 25 ft at 56 kHz
- 10 ft Cord



PART #	PKG.
280741	PKGD

## IN-WALL IR RECEIVER

- IR Receive Frequency: 34 kHz to 60 kHz
- IR Transmit Frequencies: 38 kHz & 56 kHz
- Range: 40 ft at 38 kHz & 25 ft at 56 kHz
- Dimensions: 2.75" W x 4.5" H x 1.6" D



PART #	PKG.
280740	PKGD

## IR EMITTERS

- IR Receive Frequency: 34 kHz to 60 kHz
- IR Transmit Frequencies: 38 kHz & 56 kHz
- Range: 40 ft at 38 kHz & 25 ft at 56 kHz



PART #	TYPE	PKG.
280738	SINGLE EMITTER	PKGD
280739	DUAL EMITTER	PKGD