HD 5 in 1 1080P Varifocal Outdoor Bullet with 6-60mm Lens

#### **FEATURES**

- 1080P High Definition
- AHD, TVI, CVI, 960H, and 720P 5 in 1
- Super Zoom with 6 60mm Lens
- IRs up to 220FT
- Weather-rating: IP66
- Control over Coax









0Lux with IR 4/25s







The **Angelorive** HD over Coax camera series is Bolide's latest full HD solution to date. Powered by CMOS 2.0MP image sensor and the latest Nextchip Analog High Definition (AHD) DSP, these cameras produce full HD 1080P resolution over coaxial cable infrastructure. Every **Angelorive** camera is compatible with AHD, HD-TVI, HD-CVI, Analog and 720P digital video recorders, making these cameras one of the most versatile HD video surveillance solutions in the industry.

The AngeloFive features Quickswitch technology – which enables each camera to switch between 960H and 1080p

as well as Analog, TVI, CVI, AHD modes with just a flip of a button. This feature allows the **Angelofive** to be integrated into traditional analog systems, as well as a new HD system – all in one camera. The Quickswitch also provides access to powerful features via an OSD (On Screen Display) where you can adjust the Digital Wide Dynamic Range, Backlight Compensation

# **SPECIFICATIONS**


**Output BNC** 1/3" IT Sensor Image Sensor **Auto Electronic Shutter** 4/24s ~ 1/45,000s 5°C **Effective Pixels** 1920(H) x 1080p **Gamma Characteristics** 0.45 Resolution 1080P Video Frame Rate IR Distance 220 ft. 1280 x 1080 **IR Status** Under 10 Lux by CDS Focal Length 6 - 60 mm**IR Power On CDS Auto Control Output Mode** 720P / AHD / CVI / TVI / Analog **Video Output** AHD Minimum Illumination 0.01@ (F1.2, AGC ON),

**Auto Gain Control** 

AUTO



## **Technology Format Switch Mode**



\*720P & 1080P is accessed through the On Screen Menu

#### **ENVIRONMENTAL**

**Power / Current** 12VDC (±10%)/400mA

Weather-Proof Rating IP66

**Dimension (MM)** 228(W) x 97(H) x 84 (D)

**Weight (G)** 1368g

Storage Temperature  $-40^{\circ}\text{C} \sim 60^{\circ}\text{C} \text{ RH95\% MAX}$ 

Operating Temperature -40°C ~ 55°C RH95% MAX

## **DIMENSIONS**

Length 8.9" inchesHeight 3.8" inches

Width 3.3" inches

