



CL-70v



CL-70v-6



CL-70v-8

Specifications		CL-70v
Speaker Type:	In-Ceiling	
Woofers:	6.5" polypropylene	
Tweeters:	0.75" PEI	
Power:	5-80 watts	
Impedance:	8 ohm or 70v	
70v Taps:	25,15,10,5,2.5w	
Frequency Range:	55 - 20k Hz.	
Sensitivity:	88dB	
Grill:	Aluminum mesh	
Dimensions (HWD):	9.5" (240mm) H 5.9" (150mm) W 8.25" (208mm) D	

Specifications		CL-70v-6
Speaker Type:	In-Ceiling	
Woofers:	6.5" polypropylene	
Tweeters:	0.45" PEI	
Power:	5-80 watts	
Impedance:	8 ohm or 70v	
70v Taps:	25,15,10,5,2.5w	
Frequency Range:	55 - 20k Hz.	
Sensitivity:	88dB	
Grill:	Aluminum mesh	
Dimensions (HWD):	9.5" (240mm) H 5.9" (150mm) W 8.25" (208mm) D	

Specifications		CL-70v-8
Speaker Type:	2-way outdoor	
Woofers:	8" polypropylene	
Tweeters:	1" PEI	
Power:	5-60 watts	
Impedance:	8 ohm or 70v	
70v Taps:	8 ohm or 70v/100v switchable	
Frequency Range:	55 - 20k Hz.	
Sensitivity:	89dB	
Grill:	Aluminum mesh	
Dimensions (HWD):	11" (280mm) H 7.7" (196mm) W 9.6" (245mm) D	



OL-70v



IC-1X2-70v

Specifications	OL-70v
Speaker Type:	Outdoor, 2 way 70v
Woofers:	6.5" polypropylene
Tweeters:	1" silk
Power:	120 watts
Impedance:	8 ohm or 70v
70v Taps:	2.5w - 25w S/selectable
Frequency Range:	95 - 20k Hz.
Sensitivity:	86dB
Grill:	Aluminum mesh
Dimensions (HWD):	11.9" (303mm) H 8.5" (215mm) W 7.5" (191mm) D

Specifications	IC-1x2-70v
Speaker Type:	Drop-in ceiling 70v speaker
Woofers:	8" paper cone
Tweeters:	0.75" PEI
Power:	5-80 watts
Impedance:	8 ohm or 70v
70v Taps:	4, 2, 1, 0.5, 0.25w
Frequency Range:	110Hz - 20kHz.
Sensitivity:	94dB
Grill:	Aluminum mesh
Dimensions (HWD):	12.25" (311mm) H 5" (127mm) W 24" (609mm) D