



**CSUB**  
Cubes just sound better



## CSUB

A U D I O

Compact styling with huge engineering - the new TruAudio CSUB Series is changing the rules. The extraordinary craftsmanship of this semi-gloss cube will blend smoothly into your décor, while the components inside will throw tuned, hard-hitting bass. Up to 350 watts of efficient power will let you feel what you've been missing. TruAudio dealers are raving about the cSubs.





### CSUB-8

**Speaker Type:** Powered subwoofer  
**Enclosure Design:** (2) passive radiators (one per side), sealed enclosure.  
**Woofers:** 8" polymer bonded cellulose  
**Power:** 150 watts internal amplifier  
**Frequency Range, LP:** 28-200Hz (+/-3 dB)  
**Frequency Range, LFE:** 28-200Hz (+/-3 dB)  
**Sensitivity:** 200mV@150W  
**Crossover:** 40-200Hz  
**Boost:** 8dB@40Hz  
**Inputs:** 1) RCA L/R 2) LFE 3) High Level Input  
**Grill:** MDF frame with black speaker cloth  
**Cabinet Dimensions:** 11.8" (300mm) H, 11.9" (304mm) W, 12.6" (320mm) D  
**Certifications:** CE, RCM, TUV, FCC  
**Cabinet Finish:** Black semi-gloss

Family:



UNIVERSAL

### CSUB-10


**Speaker Type:** Powered subwoofer  
**Enclosure Design:** (2) passive radiators (one per side), sealed enclosure.  
**Woofers:** 10" polymer bonded cellulose  
**Power:** 250 watts internal amplifier  
**Frequency Range, LP:** 25-200Hz (+/-3 dB)  
**Frequency Range, LFE:** 25-200Hz (+/-3 dB)  
**Sensitivity:** 200mV@250W  
**Crossover:** 40-200Hz  
**Boost:** 9dB@35Hz  
**Inputs:** 1) RCA L/R 2) LFE 3) High Level Input  
**Grill:** MDF frame with black speaker cloth  
**Cabinet Dimensions:** 13.1" (332mm) H, 13.4" (341mm) W, 13.9" (352mm) D  
**Certifications:** CE, RCM, TUV, FCC  
**Cabinet Finish:** Black semi-gloss



UNIVERSAL

### CSUB-12

**Speaker Type:** Powered subwoofer  
**Enclosure Design:** (2) passive radiators (one per side), sealed enclosure.  
**Woofers:** 12" polymer bonded cellulose  
**Power:** 350 watts internal amplifier  
**Frequency Range, LP:** 20-200Hz (+/-3 dB)  
**Frequency Range, LFE:** 20-200Hz (+/-3 dB)  
**Sensitivity:** 200mV@350W  
**Crossover:** 40-200Hz  
**Boost:** 8dB@40Hz  
**Inputs:** 1) RCA L/R 2) LFE 3) High Level Input  
**Grill:** MDF frame with black speaker cloth  
**Cabinet Dimensions:** 14.9" (380mm) H, 15.2" (385mm) W, 15.8" (402mm) D  
**Certifications:** CE, RCM, TUV, FCC  
**Cabinet Finish:** Black semi-gloss



UNIVERSAL