



Door Open
FSR350SE



Door Closed
FSR350SE

Specifications

- 16 gauge cold rolled steel
- Black powder coated

Standards

- EIA/ECA-310-E
- TIA-569-D



Splice Enclosure
FSS01S



Splice Trays
STRAY24F
STRAY12F



Fusion Splice Protection Sleeves
FSHST401025
FRSHST401025

Splice Enclosures and Hinged Rack Mount Splice Shelves

| Rack Units | Height Inches (mm) | Width Inches (mm) | Depth Inches (mm) | Splice Tray Capacity | Catalog No. |
|------------|-----------------------|----------------------|----------------------|-------------------------|----------------------------------|
| 1 | 1.75" (44) | 17" (432) | 11" (279) | 2 | FSS01S |
| 2 | 3.5" (89) | 17" (432) | 11" (279) | 6 | FCR350SE FSS02S |

Note: Splice trays not included.

Splice Trays

| No. of Fibers | Height Inches (mm) | Width Inches (mm) | Length Inches (mm) | Type | Catalog No. |
|---------------|-----------------------|----------------------|-----------------------|----------------------|---------------------|
| 12 | 0.4" (10) | 5" (127) | 7" (178) | Fusion | STRAY12F |
| | | | | Mechanical | STRAY12M |
| 24 | 0.4" (10) | 5" (127) | 10" (254) | Fusion | STRAY24F |
| | | | | Mechanical | STRAY24M |
| 144 | 0.4" (10) | 5" (127) | 10" (254) | (12X12 Ribbon) | STRAY12RFS |
| | | | | (12X12 Ribbon, Deep) | STRAY12RFSDP |

Fusion Splice Protection Sleeves

25-pack

| Fiber Type | Sleeve Length Inches (mm) | Cleave Length Inches (mm) | Sleeve Diameter After Shrink Inches (mm) | Catalog No. |
|-----------------------------------|------------------------------|------------------------------|------------------------------------------------|---------------------|
| Single, up to 900 μ m coating | 1.6" (40) | .4" (10) | 0.12" (3.1) | FSHST401025 |
| 12-fiber ribbon | 1.6" (40) | .4" (10) | 0.18" (4.5) | FRSHST401025 |