



### DISPLAY

<b>Resolution</b>	Analog: 2MP 1080P/720P/960H IP: 2MP 1080P/720P/960H
<b>Display Output</b>	1/4/6 S.E.Q.
<b>Features</b>	Control over Coax <b>Quick Connect</b>

### RECORD

<b>Resolution</b>	Analog: 1080P/720P/960H IP: 1080P/720P/960H
<b>Speed</b>	1080P:PAL:15fps(each ch) 1080P:NTSC:15fps(each ch)  720P: PAL:25fps(each ch) NTSC: 30fps(each ch)  960H: PAL:25fps(each ch) NTSC: 30fps(each ch)  IP: PAL:25fps(each ch) NTSC: 30fps(each ch)

<b>Video Compression</b>	H.264
<b>Video System</b>	NTSC/PAL
<b>Operating System</b>	Linux (embedded)
<b>Analog Video Input/Output</b>	4CH inputs/VGA & HDMI output
<b>IP Video Input</b>	Up to 6ch with 24Mbps total throughput
<b>Composite Video Input</b>	Up to 4 CH
<b>Audio Input/Output</b>	4CH inputs / 1 CH output (RCA)
<b>IP-Recording Bandwidth</b>	8 Mbps~ 24Mbps(default is 8Mbps, decrease one Analog channel can increase 4Mbps)
<b>Max. Output Bandwidth</b>	32Mbps
<b>Max. Decode Performance</b>	1080P: 2 CH Real-Time
<b>Recording Mode</b>	Continuous/Manual/Motion detect
<b>Synchronous Playback</b>	4 CH
<b>Network Type</b>	RJ45
<b>HDD Interface</b>	1 SATA HDD, up to 6TB
<b>Multiplex Operation</b>	Live display, record, playback, backup, and network
<b>USB</b>	2 x USB (for mouse and backup)
<b>Sensor &amp; Alarm I/O</b>	No
<b>PTZ Control</b>	Yes (RS-485)
<b>Mobile Surveillance</b>	Supports mobile phones: iPhone/Android
<b>VGA/HDMI</b>	1024*768, 1280*1024, 1440*900, 1920*1080
<b>Power Supply</b>	DC12V/2A
<b>Dimensions</b>	300 x 227 x 53mm
<b>Working Temperature</b>	-10°C~+55°C
<b>Working Humidity</b>	10%~90%