

## Specification Sheet

Part Number: T50R0C2



**Article Number**

111-04878

**Type**

T50R

**Color**

Black (BK)

**Features & Benefits**

- Engineered and manufactured for maximum performance and quality.
- Made from 100% high-quality plastic to ensure efficient recycling.
- Inside serration for a strong grip onto bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail allows for simpler insertion.

**Quantity Per**

bag

**Product Description**

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Standard Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Black, 100/pkg
<b>Global Part Name</b>	T50R-PA66-BK
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	8.0
<b>Length L (Metric)</b>	202.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	1.97
<b>Bundle Diameter Max (Metric)</b>	50.0

**Thickness T (Metric)**

1.2

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**US MIL SPEC**

MS3367-1-10

**Flammability**

UL 94 V2

**Halogen free**

Yes

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**ROHS Complaint**

Yes

**UL Recognized (US)**

Yes

**UL Listed (US and Canada)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

100

**Customs Number**

3926909987

---

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)