



AMPLIFIERS

TRU-S350xi - AMP-3512 - AMP-7012



TRU-S350xi



AMP-3512



AMP-7012





Specifications	TRU-S350xi
Channels:	Mono channel
Continuous Power:	250 watts/ch @ 8 ohms(per channel) 350 watts/ch @ 4 ohms(per channel)
Inputs:	LFE, 2- Pre-Amp, Line Level (Left & Right)
Impedance:	4-8 Ω
Weight:	35 lbs
Rack Mount:	Includes rack ears
Dimensions (HWD):	3.25" (82mm) H 16.5" (419mm) W 13.5" (342mm) D
Certification:	TUV, CAN/CSA, CE, RCM



Specifications	AMP-3512
Channels:	12 channels, 6 zones
Continuous Power:	35 watts/ch @ 8 Ω
Bridged Power Output:	90 watts/ch @ 8 Ω
Inputs:	2- Global Ins (BUS), 2- Global Outs (BUS), 6- Local Inputs
Impedance:	8Ω
Weight:	27.5 lbs
Rack Mount:	Includes rack ears
Dimensions (HWD):	3.9" (99mm) H 16.4" (417 mm) W 14.5" (368mm) D
Certification:	ETL, CE (or CB scheme)

Specifications	AMP-7012
Channels:	12 channels, 6 zones
Continuous Power:	70 watts/ch @ 8 Ω
Bridged Power Output:	120 watts/ch @ 8 Ω
Inputs:	2- Global Ins (BUS), 2- Global Outs (BUS), 6- Local Inputs
Impedance:	4-8Ω
Weight:	47.5 lbs
Rack Mount:	Includes rack ears
Dimensions (HWD):	6.7" (171mm) H 17" (432mm) W 16.5" (419mm) D
Certification:	ETL, CE (or CB scheme)